

Traditional Series

Model 74



Model 74 Specifications

| | |
|---|--|
| Heating Capacity | 1,500 to 2,600 sq. ft. |
| BTU/H Output | 13,300 - 52,400 |
| Emissions G/H | 1.8 |
| Firebox Volume | 2.5 cu. ft. |
| Firewood Length | 22" (side to side), 16" (front to back) |
| Ash Pan | No |
| Blower | Yes |
| Flue Size | 6" |
| Framing Dimensions | 37½"W x 34¾"H x 24¾"D |
| Pre-Fab Approved | Yes |
| Mobile Home Approved | Yes |
| Approximate Weight | 460 lbs. |
| Optional Pedestal (FA P8) (sold separately) | 10 ¼" H |
| Hearth Pad Size** | 34" W x 48" D |
| **Hearth pad size listed is the minimum size required for vertical vented installation. | |
| Requires outside air kit for mobile home installation. | |
| • Model 74 comes standard with 1½" deep rear shields not included in the stove dimension depth. | |

UNIVERSAL AND READY TO USE

The Model 74 is a non-catalytic wood-burning stove designed to meet the most stringent emissions standards without the use of a catalytic combustor. The Model 74 has a BTU rating of 52,400 and can heat up to 2,600 square feet. The 74 delivers heavy-duty heat performance and is available as a masonry fireplace, pre-tab fireplace insert or freestanding unit.

